

## NFA6702

### DC~67GHz, 2W

#### Features:

- \* Low VSWR
- \* High Attenuation Flatness

#### Applications:

- \* Wireless
- \* Transmitter
- \* Laboratory Test
- \* Radar

#### Electrical

Frequency:	DC~67GHz
Attenuation:	1~10dB, 20dB, 30dB
Impedance:	50Ω
Average Power*1:	2W@25°C max.
Peak Power:	20W (5μS pulse width, 1% duty cycle)

[1] Derated linearly to 0.5W@125°C.


#### Mechanical

RF Connectors:	1.85mm
Dielectric:	PEI
Outer Conductor:	Passivated stainless steel
Male Inner Conductor:	Gold plated brass
Female Inner Conductor:	Gold plated beryllium copper

#### Environmental

Temperature: -55~+125°C

#### Outline Drawings



Unit: mm [in]

Tolerance: ±2mm [±0.08in]

#### Attenuation Accuracy and VSWR

Frequency (GHz)	Attenuation Accuracy (±dB) vs. Attenuation (dB)			VSWR (max.)
	1~10	20	30	
DC~67	-1.0/+1.2	-1.2/+1.2	-1.5/+1.5	1.35

#### How To Order

**NFA6702-X-Y-Z**

X: Frequency in GHz

Y: Attenuation in dB

Z: Connector type

Connector naming rules:

V - 1.85mm

Examples:

To order an attenuator, DC~67GHz, 1.85mm male to 1.85mm female, 20dB attenuation, specify NFA6702-67-20-V.