

NCK-L1-9

L16 Connectors, DC~9GHz

Features:

* High Precision

Applications:

* Calibration
* Laboratory Test



Description

With the components in these kits you can make error-corrected measurements of devices supplied with L16 connectors from DC to 9 GHz.

Components

Part Number	Description	Frequency	Impedance	VSWR	Phase Accuracy	Inner Conductor	Outer Conductor	Size
		(GHz)	(Ω)	(Max.)	(°, Max.)			(mm)
NOL1C-M-9	L16 male open	DC~9	50	-	±0.8	Gold plated beryllium copper	Passivated stainless steel	-
NOL1C-F-9	L16 female open			-	±0.8			-
NSL1C-M-9	L16 male short			-	±0.8			-
NSL1C-F-9	L16 female short			-	±0.8			-
NCT-L1-C-M-9	L16 male termination			1.032	-			-
NCT-L1-C-F-9	L16 female termination			1.032	-			-
NW-L11-CK	L16 torque wrench			-	-	Nickel plated tool steel (Head)	Aluminium, anodised (Handle)	19.1 (Opening size)
NAL1L1C-MM*	L16 male to L16 male adapter			1.06	-	Gold plated beryllium copper	Passivated stainless steel	-
NAL1L1C-MF*	L16 male to L16 female adapter							-
NAL1L1C-FF*	L16 female to L16 female adapter							-
Storage Box		-	-	-	-	Wood		275*200*80/ 145*145*60

* ** Equal phase adapter

How To Order

NCK-L1-9-10 All the 10 components in one box.

NCK-L1-9-1-3M Three in one box, including open, short and termination, male, NOL1C-M-9, NSL1C-M-9, NCT-L1-C-M-9.

NCK-L1-9-1-3F Three in one box, including open, short and termination, female, NOL1C-F-9, NSL1C-F-9, NCT-L1-C-F-9.

NCK-L1-9-1-6 Six in one box, including NCK-L1-9-1-3M and NCK-L1-9-1-3F.

To order a single component, specify the part number in the first column.