

NCK-3-9-1

3.5mm Connectors, DC~9GHz, Precision type

Features:
* High Precision

Applications:
* Calibration
* Laboratory Test



Description

With the components in these kits you can make error-corrected measurements of devices supplied with 3.5mm connectors from DC to 9 GHz.

Components

Part Number	Description	Frequency	Impedance	VSWR	Phase Accuracy	Inner Conductor	Outer Conductor	Size
		(GHz)	(Ω)	(Max.)	(°, Max.)			(mm)
NO3C-M-9-1	3.5mm male open	DC~9	50	-	±0.8	Gold plated beryllium copper	Gold plated beryllium copper	-
NO3C-F-9-1	3.5mm female open			-	±0.8			-
NS3C-M-9-1	3.5mm male short			-	±0.8			-
NS3C-F-9-1	3.5mm female short			-	±0.8			-
NCT-3-C-M-9-1	3.5mm male termination			1.032	-			-
NCT-3-C-F-9-1	3.5mm female termination			1.032	-			-
NW-31-CK	3.5mm torque wrench			-	-	Nickel plated tool steel (Head)	Aluminium oxide (Handle)	8.1 (Opening size)
NA33C-MM*	3.5mm male to 3.5mm male adapter			1.06	-	Gold plated beryllium copper	Passivated stainless steel	-
NA33C-MF*	3.5mm male to 3.5mm female							-
NA33C-FF-2*	3.5mm female to 3.5mm female							-
Connect Joint	-	-	-	-	-	Plastic		-
Inner Hexagon Spanner	-	-	-	-	-	-		-
Storage Box	-	-	-	-	-	Wood		275*200*80/ 145*145*60

* ** Equal phase adapter

How To Order

NCK-3-9-1-10 All the 10 components in one box.

NCK-3-9-1-3M Three in one box, including open, short and termination, male, NO3C-M-9-1, NS3C-M-9-1, NCT-3-C-M-9-1.

NCK-3-9-1-3F Three in one box, including open, short and termination, female, NO3C-F-9-1, NS3C-F-9-1, NCT-3-C-F-9-1.

NCK-3-9-1-6 Six in one box, including NCK-3-9-1-3M and NCK-3-9-1-3F.

To order a single component, specify the part number in the first column.