

NA33

3.5mm to 3.5mm

Features:
* Low VSWR

Applications:
* Wireless
* Transmitter
* Laboratory Test
* Radar

Electrical

Frequency: DC~33GHz
VSWR: 1.15 max.
1.25 max. (bulk head)
1.25 max. (right angle)
Impedance: 50Ω

Mechanical

RF Connectors: 3.5mm
Outer Conductor: Passivated stainless steel
Dielectric: PEI
Inner Conductor: Gold plated beryllium copper
or gold plated brass

Environmental

Temperature: -55~+125°C

How To Order

NA33-MM - 3.5mm(m) to 3.5mm(m), Outline A

NA33-MF - 3.5mm(m) to 3.5mm(f), Outline B

NA33-FF - 3.5mm(f) to 3.5mm(f), Outline C

NA33R-MM - 3.5mm(m) to 3.5mm(m), right angle, Outline D

NA33R-MF - 3.5mm(m) to 3.5mm(f), right angle, Outline E


NA33R-FF - 3.5mm(f) to 3.5mm(f), right angle, Outline F

NA33L-FF - 3.5mm(f) to 3.5mm(f) flange mount, Outline G


NA33H-FF - 3.5mm(f) to 3.5mm(f) bulk head, Outline H

Customization is available upon request.


Outline Drawings




Outline A




Outline B




Outline C




Outline D




Outline E



Outline F



Outline G



Outline H

Unit: mm [in]

Tolerance: ±0.2mm [±0.008in]