

NCT-FL4G-M

TNC Connector, DC~18GHz

Features:
* Low VSWR

Applications:
* Wireless
* Radar
* Instruments
* Electronics

Electrical

Frequency:	DC~18GHz
VSWR:	1.15 max.
Impedance of Dielectric:	5000MΩ min.
Impedance of Inner Conductor:	1.5mΩ max.
Impedance of Outer Conductor:	0.2mΩ max.
Voltage Withstand:	1500V DC
Impedance:	50Ω


Mechanical

RF Connector:	TNC Female
Mating Life Cycle:	500 cycles
Outer Conductor:	Passivated SUS303 Stainless Steel
Dielectric:	PEI & PTFE
Inner Conductor:	Gold Plated Beryllium Copper


Environmental

Temperature:	-55~+165°C
--------------	------------

Outline Drawings



Part Number	ΦD1	ΦD2	L1	L2
NCT-FL4G-M80-01	4 [0.158]	0.8 [0.031]	4 [0.158]	2 [0.079]



Part Number	ΦD1	ΦD2	L1	L2
NCT-FL4G-M80-02	4 [0.158]	0.8 [0.031]	4 [0.158]	2 [0.079]

Unit: mm [in]

Tolerance: ±0.2mm [±0.008in]